

---

Subject: localized formatting of double on linux  
Posted by [lokki](#) on Tue, 30 Dec 2008 10:33:27 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

I'm porting application developed in UPP on Windows to Linux (using Gentoo 2008.1).

When formatting double values (displayed in GridCtrl, in EditDouble), strange output appears.  
Following converter worked on windows but gives strange results on linux

```
class ConvertMoney : public ConvertDouble
{
public: ConvertMoney() : ConvertDouble() {Pattern("%2!nl");}
};
```

e.g. when we have in database value 1.234, on windows is displayed string "1,23", on linux "1,00".  
It always changes last two characters with zeros. Experimenting with converter's pattern gives no acceptable results.

My linux locale is:

```
LANG=sk_SK.utf8
LC_CTYPE=sk_SK.utf8
LC_NUMERIC="sk_SK.utf8"
LC_TIME="sk_SK.utf8"
LC_COLLATE=C
LC_MONETARY="sk_SK.utf8"
LC_MESSAGES="sk_SK.utf8"
LC_PAPER="sk_SK.utf8"
LC_NAME="sk_SK.utf8"
LC_ADDRESS="sk_SK.utf8"
LC_TELEPHONE="sk_SK.utf8"
LC_MEASUREMENT="sk_SK.utf8"
LC_IDENTIFICATION="sk_SK.utf8"
LC_ALL=
```

At the beginning of code, the language is set:

```
int language = LNGC_('S','K','S','K', CHARSET_UTF8);
SetLanguage(language);
```

Database is Postgresql 8.3,

Thanks in advance for any clue.

---

---

Subject: Re: localized formatting of double on linux  
Posted by [cocob](#) on Tue, 30 Dec 2008 15:25:01 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

gtk\_init() change libc behaviour according to locale setting.

I use this to remove the problems

```
setlocale(LC_ALL,"C");
```

---

---

Subject: Re: localized formatting of double on linux  
Posted by [lokki](#) on Tue, 30 Dec 2008 15:59:16 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Thanks a lot. Looks like it works now

---

---

Subject: Re: localized formatting of double on linux  
Posted by [lokki](#) on Sat, 03 Jan 2009 11:21:22 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

bad news

As posted previously, on Gentoo it works fine (development machine). Now trying to run Gentoo built executable on Ubuntu 10.8 ("production" machine). Same problem, the workaround for Gentoo doesn't work on Ubuntu. Don't know why, because locale on Ubuntu is set to:

```
LANG=sk_SK.UTF-8
LC_CTYPE="sk_SK.UTF-8"
LC_NUMERIC="sk_SK.UTF-8"
LC_TIME="sk_SK.UTF-8"
LC_COLLATE="sk_SK.UTF-8"
LC_MONETARY="sk_SK.UTF-8"
LC_MESSAGES="sk_SK.UTF-8"
LC_PAPER="sk_SK.UTF-8"
LC_NAME="sk_SK.UTF-8"
LC_ADDRESS="sk_SK.UTF-8"
LC_TELEPHONE="sk_SK.UTF-8"
LC_MEASUREMENT="sk_SK.UTF-8"
LC_IDENTIFICATION="sk_SK.UTF-8"
LC_ALL=
```

I tried to modify workaround a for whole locale configuration:

```
...
setlocale(LC_COLLATE,"sk_SK.UTF-8");
setlocale(LC_MONETARY,"sk_SK.UTF-8");
setlocale(LC_MESSAGES,"sk_SK.UTF-8");
...
setlocale(LC_ALL,"C");
```

But this doesn't help at all.

Thanks for any suggestions

---

Subject: Re: localized formatting of double on linux  
Posted by [cocob](#) on Sat, 03 Jan 2009 13:57:29 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

do you use setlocale(LC\_ALL,"C"); after GUI initialization ?

---

---

Subject: Re: localized formatting of double on linux  
Posted by [lokki](#) on Sat, 03 Jan 2009 14:09:57 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

I don't know when the GUI is initialised exactly. I set language and locale in first lines of GUI\_APP\_MAIN. The code looks like this...

```
GUI_APP_MAIN
{
    int language = LNGC_('S','K','S','K', CHARSET_UTF8);
    SetLanguage(language);
    setlocale(LC_ALL,"C");
    ....
```

edit: So it is executed before the main window is instantiated and run.

---

---

Subject: Re: localized formatting of double on linux  
Posted by [cocob](#) on Sun, 04 Jan 2009 10:55:54 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

I think this is the problem.

In my app i use setLocal in my main window constructor

---

---

Subject: Re: localized formating of double on linux  
Posted by [lokki](#) on Mon, 05 Jan 2009 19:11:35 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

OK, tried and didn't work.

I'm going to investigate it furher, but I'm very surprised. I wouldn't believe such thigs can happen between two unix systems (running same executable/source).

Looks to me, like I have something set up differently according to localization in Ubuntu (I checked locale variables, but don't know what else to check.. libc version??...)

Thanks for help cocob, in Gentoo it works perfectly (but not Ubuntu).

---

---

Subject: Re: localized formating of double on linux  
Posted by [lokki](#) on Mon, 05 Jan 2009 19:48:02 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

deleted (duplicate message)

---

---

Subject: Re: localized formating of double on linux  
Posted by [lokki](#) on Sun, 01 Feb 2009 17:37:56 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

just to let you know, after experimenting with Ubuntu, I didn't find any solution of this problem. Switching production environment to Open SUSE 11.1 running KDE helped. Probably GNOME on Ubuntu was causing the problem some way, I wasn't able to resolve. Devel Gentoo was running KDE as well, that's why I think this way. Development machine was swithced to Open SUSE afterwards as well.

---

---

Subject: Re: localized formating of double on linux  
Posted by [zsolt](#) on Tue, 13 Jul 2010 20:18:13 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Put an extra line into /etc/locale.alias:  
sk\_SK sk\_SK.UTF-8  
and run the command  
locale-gen

from console.

I think it would be better to fix this in UPP code and trying locale with ".UTF-8" suffix when "sk\_SK" type locale didn't succeed.

---