
Subject: GetLanguageCode

Posted by [White_Owl](#) on Mon, 05 Jan 2009 16:34:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have several localized texts in src.tpp and would like to load them in run-time according to the current user language.

The easiest way I can think of, is to do it with a code like this:

```
PromptOK(String("MyProject/src/About$") + GetLanguageCode(GetCurrentLanguage()));
```

And a function GetLanguageCode() is a slightly modified LNGasText():

```
String GetLanguageCode(int d)
```

```
{
String result;
int c = (d >> 15) & 31;
if(c) {
result.Cat(c + 'a' - 1);
c = (d >> 10) & 31;
if(c) {
result.Cat(c + 'a' - 1);
c = (d >> 5) & 31;
if(c) {
result.Cat('-');
result.Cat(c + 'a' - 1);
c = d & 31;
if(c) result.Cat(c + 'a' - 1);
}
}
}
c = (d >> 20) & 255;
return result;
```

}The change is that it does not add charset name and returns lower-case language code, exactly as TPP editor set language codes for topics.

Am I inventing a wheel?

Subject: Re: GetLanguageCode

Posted by [sergeynikitin](#) on Mon, 05 Jan 2009 18:59:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

Maybe use this code:

```
String s = String("MyProject/src/"+Topic+"$") +
String(ToLower(LNGAsText(GetCurrentLanguage())& 0xffff));
```

But I use extended form of help request

```
Vector<String> Topic = Split(topic, '#');
```

```
String s = String("MyProject/help/"+Topic[0]+"$") +
String(ToLower(LNGAsText(GetCurrentLanguage())& 0xffff))+"#" +String(Topic[1]);
```

Subject: Re: GetLanguageCode
Posted by [mirek](#) on Mon, 05 Jan 2009 21:35:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

White_Owl wrote on Mon, 05 January 2009 11:34
The easiest way I can think of, is to do it with a code like this:
`PromptOK(String("MyProject/src/About$") + GetLanguageCode(GetCurrentLanguage()));`
The change is that it does not add charset name and returns lower-case language code, exactly as TPP editor set language codes for topics.

Am I inventing a wheel?

You can use:

```
LNGAsTxt(SetLNGCharset(GetCurrentLanguage(), CHARSET_DEFAULT))
```

Mirek

Subject: Re: GetLanguageCode
Posted by [White_Owl](#) on Mon, 05 Jan 2009 21:42:04 GMT
[View Forum Message](#) <> [Reply to Message](#)

Well... After some tweaking I now load my QTF's like this:

```
Topic GetTopicLNG(const String &path) {
    return GetTopic(path + "$" + ToLower(LNGAsText(GetCurrentLanguage()).Left(5)));
}
....
```

```
PromptOK(GetTopicLNG("MyProject/src/About"));
```

May be some kind of language sensitive loading function should be in the default Topic library?

Subject: Re: GetLanguageCode
Posted by [mirek](#) on Mon, 05 Jan 2009 22:23:16 GMT
[View Forum Message](#) <> [Reply to Message](#)

White_Owl wrote on Mon, 05 January 2009 16:42Well... After some tweaking I now load my QTF's like this:

```
Topic GetTopicLNG(const String &path) {
```

```
return GetTopic(path + "$" + ToLower(LNGAsText(GetCurrentLanguage()).Left(5)));  
}  
....
```

PromptOK(GetTopicLNG("MyProject/src/About"));
May be some kind of language sensitive loading function should be in the default Topic library?

Sounds good

Should there be used the trick to remove charset too?

Mirek

Subject: Re: GetLanguageCode
Posted by [White_Owl](#) on Tue, 06 Jan 2009 14:54:25 GMT
[View Forum Message](#) <> [Reply to Message](#)

luzr wrote on Mon, 05 January 2009 23:23 Should there be used the trick to remove charset too? Yes. That is why I have .Left(5) from the result of LNGAsText().

Subject: Re: GetLanguageCode
Posted by [mirek](#) on Wed, 07 Jan 2009 12:42:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

This would work, right?:

```
Topic GetTopicLNG(const String &path) {  
    return GetTopic(path + "$" + ToLower(LNGAsTxt(SetLNGCharset(GetCurrentLanguage(),  
CHARSET_DEFAULT))));  
}
```

Maybe we could add something like

```
int LNGNoCharset(int c)  
{  
    return SetLNGCharset(GetCurrentLanguage(), CHARSET_DEFAULT);  
}
```

to avoid future confusion too

Mirek

Subject: Re: GetLanguageCode
Posted by [White_Owl](#) on Wed, 07 Jan 2009 15:50:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

luzr wrote on Wed, 07 January 2009 13:42This would work, right?:Looks like it. With some minor corrections of course

```
Topic GetTopicLNG(const String &path) {  
    return GetTopic(path + "$" + ToLower(LNGAsText(SetLNGCharset(GetCurrentLanguage()),  
CHARSET_DEFAULT))));  
}
```

I am not sure about the second one though... May be with a longer name it would be more easy to use:

```
int GetCurrentLanguageIdWithDefaultCharset()  
{  
    return SetLNGCharset(GetCurrentLanguage(), CHARSET_DEFAULT);  
}
```

But I do not actually see where this shortcut would be useful.

Subject: Re: GetLanguageCode
Posted by [mirek](#) on Fri, 09 Jan 2009 07:44:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

OK, now in Core.

Mirek
