
Subject: BSD make: strange issue
Posted by [mirek](#) on Wed, 01 Apr 2009 20:27:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

I was trying to enhance src version to build with (PC-)BSD and encountered this strange issue:

```
make: don't know how to make ide/app.tpp/Aboutn-us.tppi. Stop  
*** Error code 2
```

The offending line is obviously:

```
ide/app.tpp/About$$en-us.tppi \
```

Now it looks like BSD make for whatever reason interprets "\$\$e" as empty string. That is weird, as '\$\$' should be escape sequence for '\$', even according to BSD make manual page.

Does anybody know what is going on now here? Is there any other way how to escape '\$'?

Mirek

Subject: Re: BSD make: strange issue
Posted by [masu](#) on Thu, 02 Apr 2009 08:53:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Mirek,

try to build with gmake (should already be installed).
At least I use it for the FreeBSD port to avoid bothersome errors.

Matthias

Subject: Re: BSD make: strange issue
Posted by [victorb](#) on Thu, 02 Apr 2009 15:29:38 GMT
[View Forum Message](#) <> [Reply to Message](#)

Have you tried to enclose the filename in single quotes to prevent expansion (i.e. '<filename>') ?

Subject: Re: BSD make: strange issue
Posted by [mirek](#) on Fri, 03 Apr 2009 06:19:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

victorb wrote on Thu, 02 April 2009 11:29 Have you tried to enclose the filename in single quotes to prevent expansion (i.e. '<filename>') ?

Does not work...

Mirek

Subject: Re: BSD make: strange issue
Posted by [mirek](#) on Fri, 03 Apr 2009 11:43:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Well, there is unfortunate thing about make/gmake - gmake is not available (as command) in Linux and we need to use it in "top" makefile (see src package for details).

Any idea?

Mirek

Subject: Re: BSD make: strange issue
Posted by [masu](#) on Fri, 03 Apr 2009 12:14:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

I remember that I used \$(MAKE) inside top Makefile for 2008.1 release. This seems to be set accordingly if gmake is invoked on top Makefile (on FreeBSD). I am not sure about that, but I will investigate soon. Maybe this is also a define used by ports infrastructure only.

If it is not defined automatically one can call "make MAKE=gmake" or maybe use a wrapper script to do this (there we are ones again using shell scripts).

By the way, can you adapt Makefile export to scheme that is used for 2008.1 release that uses some variable assignments to set up commands etc.?

Matthias

Subject: Re: BSD make: strange issue
Posted by [mirek](#) on Fri, 03 Apr 2009 12:18:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

masu wrote on Fri, 03 April 2009 08:14 I remember that I used \$(MAKE) inside top Makefile for 2008.1 release. This seems to be set accordingly if gmake is invoked on top Makefile (on FreeBSD). I am not sure about that, but I will investigate soon. Maybe this is also a define used by ports infrastructure only.

If it is not defined automatically one can call "make MAKE=gmake" or maybe use a wrapper script to do this (there we are ones again using shell scripts).

By the way, can you adapt Makefile export to scheme that is used for 2008.1 release that uses some variable assignments to set up commands etc.?

Matthias

It should be basically the same, I have only changed it to use relative paths....

Mirek

Subject: Re: BSD make: strange issue
Posted by [masu](#) on Fri, 03 Apr 2009 12:25:12 GMT
[View Forum Message](#) <> [Reply to Message](#)

Replace all 'make' calls inside small Makefile with \$(MAKE), I am quite sure that 'gmake' is also called if you invoke make process with 'gmake'.

Matthias

Subject: Re: BSD make: strange issue
Posted by [mirek](#) on Fri, 03 Apr 2009 12:48:26 GMT
[View Forum Message](#) <> [Reply to Message](#)

masu wrote on Fri, 03 April 2009 08:25 Replace all 'make' calls inside small Makefile with \$(MAKE), I am quite sure that 'gmake' is also called if you invoke make process with 'gmake'.

Matthias

Well, actually, I am now considering that we should replace Makefile with "install" script...

Mirek

Subject: Re: BSD make: strange issue
Posted by [mirek](#) on Sat, 04 Apr 2009 08:25:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Well, a new issue:)

How to deal with -lld?

I mean, it says it cannot find ld...

Mirek

Subject: Re: BSD make: strange issue
Posted by [masu](#) on Tue, 07 Apr 2009 09:03:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

I never saw that on the command line.
Do you mean -ldl?

Matthias

Subject: Re: BSD make: strange issue
Posted by [mirek](#) on Tue, 07 Apr 2009 09:26:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

Yes, sorry.

Now I see that FREEBSD does not have it (in package organizer).

I guess dlopen (etc.) is in standard library.

Mirek

Subject: Re: BSD make: strange issue
Posted by [masu](#) on Tue, 07 Apr 2009 10:01:16 GMT
[View Forum Message](#) <> [Reply to Message](#)

Quote:I guess dlopen (etc.) is in standard library.
Yes it is included in libc:
[http://www.freebsd.org/cgi/man.cgi?query=dlopen&sektion= 3](http://www.freebsd.org/cgi/man.cgi?query=dlopen&sektion=3).

Matthias

Subject: Re: BSD make: strange issue
Posted by [masu](#) on Tue, 07 Apr 2009 21:05:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

I tried to use \$(MAKE) in a test makefile and it seems to be defined accordingly as gmake or make (depends on what is called).

Tested platforms:

- FreeBSD
- Linux (Ubuntu)
- OpenBSD

Matthias
