
Subject: GuiLock Example broken
Posted by [masu](#) on Mon, 17 Aug 2009 08:35:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

I tried the GuiLock example and got the following error:

Assertion failed in d:\programs\upp-svn\uppsrc\Draw\DrawLock.cpp, line 32
sGLockLevel > 0
Whereas GuiMT example works fine.
Could it be MingW causing the troubles?

System: WinXP, MingW 4.3.0, SVN 1514

Matthias

Subject: Re: GuiLock Example broken
Posted by [cocob](#) on Mon, 17 Aug 2009 08:36:46 GMT
[View Forum Message](#) <> [Reply to Message](#)

I have same type of problems with MINGW and MT.
No problems with MSC or GCC on Linux

cocob

Subject: Re: GuiLock Example broken
Posted by [mirek](#) on Mon, 17 Aug 2009 09:57:43 GMT
[View Forum Message](#) <> [Reply to Message](#)

masu wrote on Mon, 17 August 2009 04:35Hi,

I tried the GuiLock example and got the following error:

Assertion failed in d:\programs\upp-svn\uppsrc\Draw\DrawLock.cpp, line 32
sGLockLevel > 0
Whereas GuiMT example works fine.
Could it be MingW causing the troubles?

System: WinXP, MingW 4.3.0, SVN 1514

Matthias

AFAIK, there was a problem with TLS variables in mingw. sGLockLevel is TLS variable...

I am sorry, but right now we cannot support MT with mingw, to my best knowledge.

Mirek

Subject: Re: GuiLock Example broken
Posted by [koldo](#) on Mon, 17 Aug 2009 15:02:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello cocob/masu

Yes it happens the same to me.

I do not have any idea about MT but if you base on GuiMT sample you can do things that work.

Best regards
Koldo

Subject: Re: GuiLock Example broken
Posted by [masu](#) on Mon, 17 Aug 2009 16:22:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

I also added '-mthreads' flag to link command line and now the example works.
I think you simply forgot to add it at the time '-mthreads' was added to compile step for MingW long time ago.
A patch is applied for GccBuilder.cpp.

Matthias

File Attachments

1) [GccBuilder.patch](#), downloaded 504 times

Subject: Re: GuiLock Example broken
Posted by [mirek](#) on Mon, 17 Aug 2009 17:17:14 GMT
[View Forum Message](#) <> [Reply to Message](#)

Nice. Thanks a lot, patch applied.

Mirek

Subject: Re: GuiLock Example broken
Posted by [koldo](#) on Mon, 17 Aug 2009 23:38:30 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello masu

I have compiled Thelde and sample using svn 1517.


Sample now runs well with MinGW, but on closing the program I get an error. It seems to come from Windows but is in spanish (in my case).

It happens the same both in Debug and Speed versions.

Best regards
Koldo

File Attachments

1) [Error.PNG](#), downloaded 1338 times



Subject: Re: GuiLock Example broken
Posted by [masu](#) on Tue, 18 Aug 2009 11:13:31 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Koldo,

I could reproduce your problem, but I have different behavior on different machines. I observed problems on machines with different MingW version installed.
Can you make sure the right MingW binary path is the first in your PATH env variable and then try again?

Matthias

Subject: Re: GuiLock Example broken
Posted by [koldo](#) on Tue, 18 Aug 2009 12:45:05 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello masu

I use MinGW version 4.4.0.

Best regards
Koldo

Subject: Re: GuiLock Example broken
Posted by [mirek](#) on Tue, 18 Aug 2009 18:22:24 GMT
[View Forum Message](#) <> [Reply to Message](#)

To be fair, I had quite a lot problems to manage "exit".

It is not unlikely that MT code is broken - maybe it can crash in MSC or GCC/Linux too. It did not during my testing, but maybe somebody should test more intensely...

Mirek

Subject: Re: GuiLock Example broken
Posted by [masu](#) on Thu, 20 Aug 2009 15:52:29 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

attached I provide a test package for explicit TLS using pthreads.

I wanted to evaluate implicit TLS due to missing `__thread` storage qualification support on OpenBSD. What I discovered was a strange behavior with U++ Core package included.

It runs without problems when compiled in optimal mode without including U++ Core. But when I include Core U++ package I get segmentation faults all the time regardless if it is compiled in debug mode or optimal mode.

As far as I understand the only thing that is replaced by including Core package is heap implementation (in optimal mode) and since I use the heap to allocate and de-allocate memory for the TLS variables it is used instead of standard one. Is that right?

If I do not use heap allocated variables, but pre-allocated ones, I do not have any problems (This can be done by setting `TLS_PRE_ALLOC` to true).

Matthias

File Attachments

1) [pthread_tls.tgz](#), downloaded 461 times

Subject: Re: GuiLock Example broken

Posted by [mirek](#) on Fri, 21 Aug 2009 12:12:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

Memory allocator uses implicit TLS, `__thread` (in fact, it is the cornerstone of its efficiency). If that one is replaced by something not working, it explains the issue. Have you tried with `USEMALLOC`.

Another thing to mention is that Thread has, at thread exit, explicit call to release per-thread associated allocator cache. If you are not using Thread, you should call `MemoryFreeThread()`; at the end of thread. But symptoms of this would be leaks, not crashes.

Side note: allocator only replaces `new/delete`, not `alloc/free`.

Subject: Re: GuiLock Example broken

Posted by [mirek](#) on Fri, 21 Aug 2009 12:15:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

BTW, it looks like you alloc tls by 'new' and free it using 'free'.

That is a receipt of failure in any case

Mirek

Subject: Re: GuiLock Example broken

Posted by [masu](#) on Fri, 21 Aug 2009 12:19:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Mirek,

thanks for explanations, it seems, it was the call to free instead of delete that caused the crash ... (sorry about that).

I meant explicit TLS not implicit one in my prior post, will edit it to correct this one.

Thanks for now,
Matthias

Subject: Re: GuiLock Example broken

Posted by [mirek](#) on Fri, 21 Aug 2009 12:33:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

masu wrote on Fri, 21 August 2009 08:19Hi Mirek,

thanks for explanations, it seems, it was the call to free instead of delete that caused the crash ... (sorry about that).

I meant explicit TLS not implicit one in my prior post, will edit it to correct this one.

Thanks for now,
Matthias

Actually, if correct `__thread` is not available, U++ allocator cannot work in MT.

Maybe you should just USEMALLOC then... In any case, to stay on the safe side, you TLS implementation should use malloc/free (and maybe then you could use such TLS to make U++ allocator work, although any positive effects will be likely diminished by slow TLS).

Mirek

Subject: Re: GuiLock Example broken
Posted by [masu](#) on Fri, 21 Aug 2009 12:43:21 GMT
[View Forum Message](#) <> [Reply to Message](#)

luzr wrote on Fri, 21 August 2009 14:33Actually, if correct `__thread` is not available, U++ allocator cannot work in MT.

I know, thats why I get problems on OpenBSD (at least I think so, at the moment).

luzr wrote on Fri, 21 August 2009 14:33Maybe you should just USEMALLOC then... In any case, to stay on the safe side, you TLS implementation should use malloc/free (and maybe then you could use such TLS to make U++ allocator work, although any positive effects will be likely diminished by slow TLS).

Ok, thanks for the advice.

Matthias

Subject: Re: GuiLock Example broken
Posted by [koldo](#) on Sun, 23 Aug 2009 08:37:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello all

Now GuiMT sample fails in the same way in MinGW as reported in GuiLock sample in Tue, 18 August 2009. It goes ok in MSC (Windows) and Gcc (Linux)

It happens in the program end.

In Debug mode I get this:

emutls_destroy function is called from the exit() function.


Is MinGW the source of this problem ?

In new version 4.4.1 emutls.c file has been changed. However I have not found MinGW 4.4.1 binaries.

Best regards
Koldo

File Attachments

1) [demo.PNG](#), downloaded 1527 times



Subject: Re: GuiLock Example broken
Posted by [koldo](#) on Mon, 24 Aug 2009 08:26:18 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello all

Good news. Twilight Dragon Media has released their GCC/mingw32 4.4.1 version (<http://www.tdragon.net/recentgcc/>)

I have just tried GUIMT and GuiLock samples and both work.

Bad news. The samples seem to go slow. GuiLock with MSC Debug goes much faster than with MinGW Speed.

The binaries I have chosen first are without dwarf-2.

Best regards
Koldo

Addendum 1:

Unfortunately there are compiling problems using dwarf-2 version

```
Compiling GUILock sample I get:Quote:In file included from
C:/upp/out/Draw/MINGW.Debug.Debug_full.Gui.Mt\bl itz.cpp:3:
C:\upp\uppsrc\Draw\DrawLock.cpp:11: error: thread-local storage not supported for this target
In file included from C:/upp/out/Draw/MINGW.Debug.Debug_full.Gui.Mt\bl itz. sGlokLevel >
0".cpp:10:
C:\upp\uppsrc\Draw\Font.cpp:266: error: thread-local storage not supported for this target
C:\upp\uppsrc\Draw\Font.cpp:328: error: thread-local storage not supported for this target
C:\upp\uppsrc\Draw\Font.cpp:355: error: thread-local storage not supported for this target
C:\upp\uppsrc\Draw\Font.cpp:356: error: thread-local storage not supported for this target
C:\upp\uppsrc\Draw\Font.cpp:357: error: thread-local storage not supported for this target
...
```

They are related with thread__.

Addendum 2:

This is black magic for me: In Mt.h using always
#define thread__ __declspec(thread) (removing __thread) GUIMT sample works well and
GUILock stops with error "Assertion failed in ... DrawLock.cpp, line 32. sGLockLevel > 0"

Subject: Re: GuiLock Example broken
Posted by [masu](#) on Mon, 24 Aug 2009 10:23:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Koldo,

thank you for your investigation.

Implicit TLS (thread-local storage) that is used in U++ is not always supported, depending on
Compiler and OS support.

It is declared by using __declspec(thread) var for MSC and __thread for GCC.

That is why you see problems with GUILock example since it depends on having sGLockLevel
variable locally available in all threads which does not seem to be supported with dwarf-2 version.
AFAIK GuiMT example does not need to use thread-local variables, that is why it works.

I have the same problems with OpenBSD that is why I try to find a solution for systems (Compiler
and OS combinations) that do not support implicit TLS.

Regards,
Matthias

Subject: Re: GuiLock Example broken

Posted by [koldo](#) on Wed, 26 Aug 2009 07:10:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thank you Matthias+Mirek

Finally I will left TDM 4.4.1 as non-dwarf version makes very slow programs and dwarf version with "Speed" option cannot link the programs. It seems it has to be polished.

To work I have returned to MinGW 4.4.0 using GuiMT concepts and voiding `__thread` in line 10 of `Mt.h`, so that now the programs end well without the `emutls_destroy` problem reported before.

I understand Mirek, but under Windows I do not want to depend only on MSC so I prefer to use something worse than `GuiLock` __, but more portable.

Best regards

Koldo

Subject: Re: GuiLock Example broken

Posted by [masu](#) on Wed, 26 Aug 2009 08:33:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Koldo,

at the moment I am working on integrating explicit TLS support into Core and Draw. Basically I replace all `thread__` variables with another per Thread mechanism to have them thread-local.

For now I managed to have a working version for console apps using `pthread` lib (only tested in OpenBSD at the moment).

But I will extend it to also include explicit TLS on Win32 for compilers that do not support it.

Regards,

Matthias

Subject: Re: GuiLock Example broken

Posted by [koldo](#) on Wed, 26 Aug 2009 18:40:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thank you Matthias

I wonder if there is somebody out there that has done something like this before. But thank you again for your efforts.

Best regards

Koldo

Subject: Re: GuiLock Example broken
Posted by [Novo](#) on Thu, 27 Aug 2009 03:57:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

koldo wrote on Mon, 24 August 2009 04:26
Good news. Twilight Dragon Media has released their GCC/mingw32 4.4.1 version
(<http://www.tdragon.net/recentgcc/>)

I have just tried GUIMT and GuiLock samples and both work.

This problem seems to be fixed in recent versions of gcc.

<http://www.mail-archive.com/gcc-bugs@gcc.gnu.org/msg258414.html>
<http://www.mail-archive.com/gcc-bugs@gcc.gnu.org/msg258420.html>

Subject: Re: GuiLock Example broken
Posted by [masu](#) on Thu, 27 Aug 2009 11:50:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

Thank you Novo for the hint.

I installed latest version (tdm-mingw-1.908.0-4.4.1.exe), but unfortunately speed of GuiLock example is very very slow (1 minute min.), now.

So, it is not worth to update to latest version.

Regards,
Matthias

Subject: Re: GuiLock Example broken
Posted by [koldo](#) on Tue, 13 Oct 2009 12:13:03 GMT
[View Forum Message](#) <> [Reply to Message](#)

New news in post http://www.ultimatepp.org/forum/index.php?t=msg&goto=23352&#msg_23352
