Subject: Back in HelpWindow crashes the application
Posted by dolik.rce on Sat, 03 Oct 2009 15:06:06 GMT
View Forum Message <> Reply to Message

Hi,

I've noticed, that hitting "Back" button in HelpWindow causes segfault if compiled with DEBUG flag. This is not critical bug, as long as it works in release mode, but I thought you should know

I discovered this while writing help for my application, but it happens in other apps too. You can use PieTest from bazaar as a test case. Precise series of actions leading to crash PieTest is:
Run the application compiled in DEBUG mode
Click "?" button to open HelpWindow
Click on topic Page2
Click "Back" buttonIf I run it in debugger, last available backtrack (one more step leads to Panic() call) readsUpp::AtomicInc (t=@0x6565723e) at /media/other/opt/uppsvn/uppsrc/Core/Mt.h:456
Upp::String0::LSet (this=0xbff70b7c, s=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/Core/String.cpp:23
Upp::String0::Assign (this=0xbff70b7c, s=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/Core/String.h:218
Upp::String::operator= (this=0xbff70b7c, s=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/Core/String.h:301
Upp::HelpWindow::GoTo0 (this=0xbff6f9a4, link=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/Help.cpp:31
Upp::HelpWindow::Back (this=0xbff6f9a4) at /media/other/opt/uppsvn/uppsrc/CtrlLib/Help.cpp:64
Upp::CallbackMethodAction<Upp::HelpWindow, void (Upp::HelpWindow::*)()>::Execute
(this=0xb78c6260) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:31
Upp::Callback::Execute (this=0xb7f49898) at
/media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xb7f49898) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::ToolButton::LeftUp (this=0xb7f49830) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/ToolButton.cpp:286
Upp::Ctrl::MouseEvent (this=0xb7f49830, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336664, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:135
Upp::Ctrl::MouseEventH (this=0xb7f49830, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336528, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:89
Upp::Ctrl::MEvent0 (this=0xb7f49830, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336320, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:293
Upp::Ctrl::DispatchMouseEvent (this=0xb7f49830, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336088, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff709f4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =

-1074335864, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff70958, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074335640, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff6f9a4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074335436, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouse (this=0xbff6f9a4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074334688, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:530
Upp::Ctrl::EventProc (this=0xbff6f9a4, w=@0xb78c9610, event=0xbff6f7bc) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Proc.cpp:347
Upp::TopWindow::EventProc (this=0xbff6f9a4, w=@0xb78c9610, event=0xbff6f7bc) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWinX11.cpp:57
Upp::Ctrl::ProcessEvent (event=0xbff6f7bc) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:238
Upp::Ctrl::EventLoop0 (ctrl=0xbff6f9a4) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:367
Upp::CallbackActionCallArg<void (*)(Upp::Ctrl*), Upp::Ctrl*, unsigned int>::Execute
(this=0xb78c61a0) at /media/other/opt/uppsvn/uppsrc/Core/Callback.h:53
Upp::Callback::Execute (this=0xbff6f89c) at /media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xbff6f89c) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::Ctrl::Call (cb={<Upp::Moveable<Upp::Callback, Upp::EmptyClass>> = {<Upp::EmptyClass>
= {<No data fields>}, <No data fields>}, action = 0xbff6f89c}) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:118
Upp::Ctrl::EventLoop (ctrl=0xbff6f9a4) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:189
Upp::TopWindow::Run (this=0xbff6f9a4, appmodal=false) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWindow.cpp:312
Upp::TopWindow::Execute (this=0xbff6f9a4) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWindow.cpp:331
PieTest::Help (this=0xbff718d0) at /media/other/opt/uppsvn/bazaar/PieTest/main.cpp:94
Upp::CallbackMethodAction<PieTest, void (PieTest::*)()>::Execute (this=0xb7f52770) at
/media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:31
Upp::Callback::Execute (this=0xbff71f2c) at /media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xbff71f2c) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::Pusher::PerformAction (this=0xbff71ec4) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/Button.cpp:16
Upp::Pusher::FinishPush (this=0xbff71ec4) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/Button.cpp:98
Upp::Pusher::LeftUp (this=0xbff71ec4) at /media/other/opt/uppsvn/uppsrc/CtrlLib/Button.cpp:56
Upp::Ctrl::MouseEvent (this=0xbff71ec4, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074328152, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:135
Upp::Ctrl::MouseEventH (this=0xbff71ec4, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074328016, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:89

Upp::Ctrl::MEvent0 (this=0xbff71ec4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074327808, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:293
Upp::Ctrl::DispatchMouseEvent (this=0xbff71ec4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074327576, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff718d0, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074327372, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouse (this=0xbff718d0, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074326624, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:530
Upp::Ctrl::EventProc (this=0xbff718d0, w=@0xb7f50910, event=0xbff7173c) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Proc.cpp:347
Upp::TopWindow::EventProc (this=0xbff718d0, w=@0xb7f50910, event=0xbff7173c) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWinX11.cpp:57
Upp::Ctrl::ProcessEvent (event=0xbff7173c) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:238
Upp::Ctrl::EventLoop0 (ctrl=0xbff718d0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:367
Upp::CallbackActionCallArg<void (*)(Upp::Ctrl*), Upp::Ctrl*, unsigned int>::Execute
(this=0xb7f52620) at /media/other/opt/uppsvn/uppsrc/Core/Callback.h:53
Upp::Callback::Execute (this=0xbff7181c) at
/media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xbff7181c) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::Ctrl::Call (cb={<Upp::Moveable<Upp::Callback, Upp::EmptyClass>> = {<Upp::EmptyClass>
= {<No data fields>}, <No data fields>}, action = 0xbff7181c}) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:118
Upp::Ctrl::EventLoop (ctrl=0xbff718d0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:189
Upp::TopWindow::Run (this=0xbff718d0, appmodal=false) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWindow.cpp:312
GuiMainFn_ () at /media/other/opt/uppsvn/bazaar/PieTest/main.cpp:127
main (argc=0, argv=0x0, envptr=0x0) at /media/other/opt/uppsvn/bazaar/PieTest/main.cpp:125
I've tried with Upp releases 1585 and 1603, using g++-4.3 in Ubuntu 9.04.

Regards,
Honza

Subject: Re: Back in HelpWindow crashes the application
Posted by mirek on Sat, 03 Oct 2009 17:43:28 GMT
View Forum Message <> Reply to Message

dolik.rce wrote on Sat, 03 October 2009 11:06Hi,

I've noticed, that hitting "Back" button in HelpWindow causes segfault if compiled with DEBUG flag. This is not critical bug, as long as it works in release mode, but I thought you should know

I discovered this while writing help for my application, but it happens in other apps too. You can use PieTest from bazaar as a test case. Precise series of actions leading to crash PieTest is:
 Run the application compiled in DEBUG mode
 Click "?" button to open HelpWindow
 Click on topic Page2
 Click "Back" buttonIf I run it in debugger, last available backtrack (one more step leads to Panic() call) readsUpp::AtomicInc (t=@0x6565723e) at /media/other/opt/uppsvn/uppsrc/Core/Mt.h:456
Upp::String0::LSet (this=0xbff70b7c, s=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/Core/String.cpp:23
Upp::String0::Assign (this=0xbff70b7c, s=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/Core/String.h:218
Upp::String::operator= (this=0xbff70b7c, s=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/Core/String.h:301
Upp::HelpWindow::GoTo0 (this=0xbff6f9a4, link=@0xb7f4f9d4) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/Help.cpp:31
Upp::HelpWindow::Back (this=0xbff6f9a4) at /media/other/opt/uppsvn/uppsrc/CtrlLib/Help.cpp:64
Upp::CallbackMethodAction<Upp::HelpWindow, void (Upp::HelpWindow::*)()>::Execute
(this=0xb78c6260) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:31
Upp::Callback::Execute (this=0xb7f49898) at
/media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xb7f49898) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::ToolButton::LeftUp (this=0xb7f49830) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/ToolButton.cpp:286
Upp::Ctrl::MouseEvent (this=0xb7f49830, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336664, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:135
Upp::Ctrl::MouseEventH (this=0xb7f49830, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336528, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:89
Upp::Ctrl::MEvent0 (this=0xb7f49830, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336320, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:293
Upp::Ctrl::DispatchMouseEvent (this=0xb7f49830, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074336088, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff709f4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074335864, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff70958, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074335640, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff6f9a4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074335436, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouse (this=0xbff6f9a4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =

-1074334688, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:530
Upp::Ctrl::EventProc (this=0xbff6f9a4, w=@0xb78c9610, event=0xbff6f7bc) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Proc.cpp:347
Upp::TopWindow::EventProc (this=0xbff6f9a4, w=@0xb78c9610, event=0xbff6f7bc) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWinX11.cpp:57
Upp::Ctrl::ProcessEvent (event=0xbff6f7bc) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:238
Upp::Ctrl::EventLoop0 (ctrl=0xbff6f9a4) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:367
Upp::CallbackActionCallArg<void (*)(Upp::Ctrl*), Upp::Ctrl*, unsigned int>::Execute
(this=0xb78c61a0) at /media/other/opt/uppsvn/uppsrc/Core/Callback.h:53
Upp::Callback::Execute (this=0xbff6f89c) at /media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xbff6f89c) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::Ctrl::Call (cb={<Upp::Moveable<Upp::Callback, Upp::EmptyClass>> = {<Upp::EmptyClass>
= {<No data fields>}, <No data fields>}, action = 0xbff6f89c}) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:118
Upp::Ctrl::EventLoop (ctrl=0xbff6f9a4) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:189
Upp::TopWindow::Run (this=0xbff6f9a4, appmodal=false) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWindow.cpp:312
Upp::TopWindow::Execute (this=0xbff6f9a4) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/TopWindow.cpp:331
PieTest::Help (this=0xbff718d0) at /media/other/opt/uppsvn/bazaar/PieTest/main.cpp:94
Upp::CallbackMethodAction<PieTest, void (PieTest::*)()>::Execute (this=0xb7f52770) at
/media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:31
Upp::Callback::Execute (this=0xbff71f2c) at /media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xbff71f2c) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::Pusher::PerformAction (this=0xbff71ec4) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/Button.cpp:16
Upp::Pusher::FinishPush (this=0xbff71ec4) at
/media/other/opt/uppsvn/uppsrc/CtrlLib/Button.cpp:98
Upp::Pusher::LeftUp (this=0xbff71ec4) at /media/other/opt/uppsvn/uppsrc/CtrlLib/Button.cpp:56
Upp::Ctrl::MouseEvent (this=0xbff71ec4, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074328152, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:135
Upp::Ctrl::MouseEventH (this=0xbff71ec4, event=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074328016, y = 0}, zdelta=0, keyflags=0) at
/media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:89
Upp::Ctrl::MEvent0 (this=0xbff71ec4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074327808, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:293
Upp::Ctrl::DispatchMouseEvent (this=0xbff71ec4, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074327576, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552
Upp::Ctrl::DispatchMouseEvent (this=0xbff718d0, e=145, p={<Upp::Moveable<Upp::Point_<int>,
Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x =
-1074327372, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:552

Upp::Ctrl::DispatchMouse (this=0xbff718d0, e=145, p={<Upp::Moveable<Upp::Point_<int>, Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, x = -1074326624, y = 0}, zd=0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMouse.cpp:530
Upp::Ctrl::EventProc (this=0xbff718d0, w=@0xb7f50910, event=0xbff7173c) at /media/other/opt/uppsvn/uppsrc/CtrlCore/X11Proc.cpp:347
Upp::TopWindow::EventProc (this=0xbff718d0, w=@0xb7f50910, event=0xbff7173c) at /media/other/opt/uppsvn/uppsrc/CtrlCore/TopWinX11.cpp:57
Upp::Ctrl::ProcessEvent (event=0xbff7173c) at /media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:238
Upp::Ctrl::EventLoop0 (ctrl=0xbff718d0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/X11Wnd.cpp:367
Upp::CallbackActionCallArg<void (*)(Upp::Ctrl*), Upp::Ctrl*, unsigned int>::Execute (this=0xb7f52620) at /media/other/opt/uppsvn/uppsrc/Core/Callback.h:53
Upp::Callback::Execute (this=0xbff7181c) at /media/other/opt/uppsvn/uppsrc/Core/Callback.cpp:11
Upp::Callback::operator() (this=0xbff7181c) at /media/other/opt/uppsvn/uppsrc/Core/Cbgen.h:63
Upp::Ctrl::Call (cb={<Upp::Moveable<Upp::Callback, Upp::EmptyClass>> = {<Upp::EmptyClass> = {<No data fields>}, <No data fields>}, action = 0xbff7181c}) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:118
Upp::Ctrl::EventLoop (ctrl=0xbff718d0) at /media/other/opt/uppsvn/uppsrc/CtrlCore/CtrlMt.cpp:189
Upp::TopWindow::Run (this=0xbff718d0, appmodal=false) at /media/other/opt/uppsvn/uppsrc/CtrlCore/TopWindow.cpp:312
GuiMainFn_ () at /media/other/opt/uppsvn/bazaar/PieTest/main.cpp:127
main (argc=0, argv=0x0, envptr=0x0) at /media/other/opt/uppsvn/bazaar/PieTest/main.cpp:125
I've tried with Upp releases 1585 and 1603, using g++-4.3 in Ubuntu 9.04.

Regards,
Honza

Thank you, fixed. (Will commit tomorrow).

Mirek
