
Subject: why not `StaticText::SetData != StaticText::SetText`

Posted by [kohait00](#) on Fri, 03 Dec 2010 10:29:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

hi guys

`StaticText` and `Label` have empty `GetData()` / `SetData()` and one cant set the text trough them. but it'd be great is there a reason why?

wo why not mapping `GetData` / `SetData` to `GetText` / `SetText` i.e.:

```
virtual void SetData(const Value& v) { SetText(AsString(v)); }  
virtual Value GetData() const { return GetText(); }
```

note the conversion above, to surely be able to display everyting..

or do `StaticText` / `Label` have special implications in terms of `Ctrl` usage?

i know of `DataPusher`, which is sort of sth like the same, isn't it?
but for `StaticText` `Label`, it'd be really great as well

Subject: Re: why not `StaticText::SetData != StaticText::SetText`

Posted by [koldo](#) on Fri, 03 Dec 2010 10:56:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

I agree.

Subject: Re: why not `StaticText::SetData != StaticText::SetText`

Posted by [kohait00](#) on Fri, 03 Dec 2010 11:09:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

i asked mirek once for `ProgressIndicator`...

http://www.ultimatepp.org/forum/index.php?t=msg&goto=29335&#msg_29335

hi response is sort of logical,

Quote:

Not quite sure it is completely right:

`ProgressIndicator` is kind of static value - user cannot change it. So far the policy was that only widgets that are editable have `Value`.

The reason is that if you want to store all user supplied values in the dialog, you can simply go

through all widgets and store the value if it is not Value::Void - that indicates that the widget does not have associated value.

but i'd prefer to have them all be accessible via the GetSetData as well, and in case of restoring sth..just make sure that exceptions are reinitialized well after restoring..

Subject: Re: why not StaticText::SetData != StaticText::SetText

Posted by [mirek](#) on Fri, 03 Dec 2010 12:54:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

I am sorry, but my "sort of logical" explanation still stands

SetData = SetText for Label would result in problems with "mass" processing.

All in all, it would even mean breaking the code compatibility.

Mirek

Subject: Re: why not StaticText::SetData != StaticText::SetText

Posted by [kohait00](#) on Fri, 03 Dec 2010 13:12:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

got it...

what 'mass' processing?

Subject: Re: why not StaticText::SetData != StaticText::SetText

Posted by [mirek](#) on Sat, 04 Dec 2010 15:15:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

kohait00 wrote on Fri, 03 December 2010 08:12got it...

what 'mass' processing?

E.g. storing the content of dialog to disk using its Serialize...

Or creating backup for Cancel.