
Subject: Wrapping text in ArrayCtrl cells

Posted by [bushman](#) on Thu, 03 Feb 2011 22:14:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

How to add text rows to an ArrayCtrl, keeping cell widths constant, and at the same time resizing when it does not fit cell size.

```
// in .h file:
```

```
ArrayCtrl wraparray;
```

```
...
```

```
// somewhere in code initialization:
```

```
wraparray.AddColumn().Ctrls(THISBACK(CreateDocEdit));
```

```
...
```

```
// DocEdit factory callback:
```

```
MyProg::CreateDocEdit(One<Ctrl>& x)
```

```
{  
    x.Create<DocEdit>().NoBackground().SetFrame(NullFrame()).Disable();  
}
```

```
...
```

```
// Adding rows: here's where I guess things go wrong!
```

```
void MyProg::AddRowsToWrapArray(Vector<Value>& rows)
```

```
{  
    int line, cy_height;  
    const int FONT_HEIGHT = GetTextSize("text sample", GetStdFont()).cy;
```

```
// this is weird, but necessary, or last included row won't show properly:
```

```
if(wraparray.GetCount() > 0)  
    wraparray.Remove(wraparray.GetCount() - 1);
```

```
for(int ix = 0; ix < rows.GetCount(); ix++) {  
    wraparray.Add(rows[ix]);  
    line = wraparray.GetCount() - 1;  
    DocEdit * de = (DocEdit*)wraparray.GetCtrl(line, 0);  
    cy_height = (de->GetLineCount() + 1)*FONT_HEIGHT;  
    de->SetRectY(0, cy_height);  
    wraparray.SetLineCy(line, cy_height);  
    de->RefreshLayout();  
}
```

```
// this is weird, but necessary, or last included row won't show properly:  
wraparray.Add();  
}
```

the DocEdit's do not seem to resize right, and I really would not like that the DocEdit scrollbars showed up for scrolling down hidden text because of wrong resizing.

What am I doing wrong?

Is there another simpler way of doing it?

Could it be possible to have a method like "void SetWrapLines(bool wrap = true);" for ArrayCtrl?

Thanks!!

Subject: Re: Wrapping text in ArrayCtrl cells
Posted by [mirek](#) on Fri, 04 Feb 2011 15:08:41 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a little bit tricky, as ArrayCtrl itself never changes the cellheight - you would have to somehow adjust it from client code.

Subject: Re: Wrapping text in ArrayCtrl cells
Posted by [bushman](#) on Fri, 04 Feb 2011 15:34:55 GMT
[View Forum Message](#) <> [Reply to Message](#)

Actually, I did a few tests in which I prompted the de->GetLineCount() and it ALWAYS returns 1,

the current number of text lines in the TextCtrl?

The Upp Text.h code source gives me something like

```
int GetLineCount() const { return line.GetCount(); } , where Vector<Ln> line; is a Vector, in which  
apparently each Ln struct corresponds to a wrapped line string in the TextCtrl view. How come it  
always return 1?
```

Thank you again

Subject: Re: Wrapping text in ArrayCtrl cells
Posted by [bushman](#) on Fri, 04 Feb 2011 19:06:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

I guess I found a solution to this issue myself; I'm using RichTextCtrl's instead of DocEdit's:

```
// this time around, wraparray ctrl factory callback creates RichTextCtrls instead:
```

```

void MyProg::CreateRichText(One<Ctrl>& x)
{
    x.Create<RichTextCtrl>().NoSb();
}

void MyProg::AddRowsToWrapArray(Vector<Value>& rows)
{
    int line, height;
    String str;
    for(int ix = 0; ix < rows.GetCount(); ix ++) {
// enter cell text as QTF:
        str = "[G1 " + rows[ix].ToString() + "]"; // G => make sure StdFont is used
        wraparray.Add(str);
        line = wraparray.GetCount() - 1;
// Get back pointer to cell RichTextCtrl
        RichTextCtrl * ra = (RichTextCtrl*)wraparray.GetCtrl(line, 0);
// Here's da trick!
        height = ::GetSmartTextHeight("\1" + str, ra->GetRect().Width()); // "\1" => tell function it's QTF
// resize both, RichTextCtrl and ArrayCtrl cell heights:
        ra->SetRectY(0, height);
        wraparray.SetLineCy(line, height);
        wraparray.RefreshLayoutDeep();
    }
}

```

It works perfectly!
Thank you.

Subject: Re: Wrapping text in ArrayCtrl cells
 Posted by [mirek](#) on Fri, 18 Feb 2011 12:06:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

kroplniczki wrote on Fri, 04 February 2011 10:34: Actually, I did a few tests in which I prompted the
 TextCtrl::GetLineCount() supposed to return the current number of text lines in the TextCtrl?

Well, it can be a little bit confusing, but it actually returns a number of paragraphs. But then, this is the main difference between DocEdit and LineEdit - DocEdit treats lines (defines as something that ends with '\n'), LineEdit as lines (does not do wordwrap).

Mirek

Subject: Re: Wrapping text in ArrayCtrl cells
Posted by [mirek](#) on Fri, 18 Feb 2011 12:07:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

kropniczki wrote on Fri, 04 February 2011 14:06I guess I found a solution to this issue myself; I'm using RichTextCtrl's instead of DocEdit's:

Well, that is a smarter solution anyway

Mirek
