

---

Subject: Simulate a button click  
Posted by [Mircode](#) on Sun, 07 Oct 2012 18:18:50 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hi there!

My application shows a keyboard made of pusher-buttons. If the user clicks a button with the mouse, the keystroke gets simulated. On the other hand, if the user physically presses a key on his keyboard, the pusher has to look pushed as long as the user holds the key.

How can I do that?

PseudoPush almost does the trick, except it releases immediately. I dont know if the KeyPush() method would help, but its protected.

Ah, and I dont want to assign a hotkey to the pusher or something like that, I want to be able to make the button look pushed from anywhere in my code.

Thanks for help in advance!

Greetings,  
Mirko

---

---

Subject: Re: Simulate a button click  
Posted by [Mircode](#) on Wed, 10 Oct 2012 20:13:30 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Inspired by this <http://www.ultimatepp.org/forum/index.php?t=msg&th=6949&start=0> I found a way:

The PseudoPush method is defined in Button.cpp and is actually very simple.

```
void Pusher::PseudoPush() {  
    if(IsReadOnly() || !IsEnabled()) return;  
    KeyPush();  
    Sync();  
    Sleep(50);  
    FinishPush();  
}
```

Now I created my own class, which offers the PseudoDown and the PseudoUp method.

```
class MyButton:public Button{  
public:  
    MyButton() {}  
    ~MyButton() {}
```

```
void PseudoDown(){  
    if(IsReadOnly() || !IsEnabled()) return;  
    KeyPush();  
    Sync();  
}  
void PseudoUp(){  
    FinishPush();  
}  
};
```

Works fine

---

---

Subject: Re: Simulate a button click  
Posted by [Mindtraveller](#) on Wed, 10 Oct 2012 23:34:59 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Cool, thanks!

---