

---

Subject: Latest TheIDE builds fail to execute under FreeBSD

Posted by [Mindtraveller](#) on Sun, 31 Aug 2014 22:45:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I have rather old version of TheIDE (oct'2013) running under FreeBSD 9.

After updating sources to latest build 7629, I've tried to rebuild TheIDE.

New executable fails to start with message:

Quote:terminate called after throwing an instance of 'Upp::LoadingError'

After renaming ~/.upp/theide directory, TheIDE starts with 'Initial setting wizard'. After setting 'Manual' sources management, I recreate sources assembly for work projects. Opening any existing package again leads to TheIDE crash with message:

Quote:terminate called after throwing an instance of 'Upp::Parser::Error'

Trying to create new project in the newly created assembly leads to TheIDE crash with the same error message.

Is there any idea how to make TheIDE work, or should I use debugger to help fixing this bug?

P.S. Please feel free to move this topic to any suitable subforum.

---

---

Subject: Re: Latest TheIDE builds fail to execute under FreeBSD

Posted by [dolik.rce](#) on Mon, 01 Sep 2014 04:55:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi Mindtraveller,

The first error was probably caused by out-of-date format of files in .upp/theide/cfg, it happened to me in past too. You correctly fixed that by renaming the directory and creating new setup.

As for the second error, I'd have a wild guess that the setup wizard might have generated wrong content in the assembly files. Can you inspect ~/.upp/theide/\*.var and check if you see something wrong? By the way, it should be safe to copy the \*.var files from your previous installation into this new one, so you don't have to set everything up again. Also if there is problem with the files, copying the old ones should help.

If all else fails, debugger is your friend :) At least knowing which function throws the exception would help a lot.

Best regards,  
Honza

---

---

Subject: Re: Latest TheIDE builds fail to execute under FreeBSD

Posted by [Sender Ghost](#) on Wed, 17 Sep 2014 14:39:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello, Pavel.

Mindtraveller wrote on Sun, 31 August 2014 22:45I have rather old version of TheIDE (oct'2013) running under FreeBSD 9.

After updating sources to latest build 7629, I've tried to rebuild TheIDE.

New executable fails to start

The TheIDE uses -O3 optimization level for GCC builder in case of "Optimize for speed" option, which also used for Optimal build mode. In my experience, the -O3 optimization level could cause runtime errors. I think, you could try to build with Size build mode or change -O3 to -O2 for GCC build method.

Currently, I run FreeBSD 10.0-RELEASE-p9 amd64 version. For purpose of testing, I created devel/upp-nightly port, based on devel/upp. It uses Nightly builds source archives, with some development changes (like depending on devel/libexecinfo) from stable version. I created a package with using poudriere on FreeBSD 9.3-RELEASE-p2 amd64 clean environment.

I think, if first method doesn't work, you could try to build devel/upp-nightly port (e.g. by using make or portmaster: portmaster -Bd devel/upp-nightly). It may install necessary dependencies. Also you could try to use already built package, in case of amd64 version (but you might need to install pkg and convert package database to use \*.txz package format): pkg add upp-nightly-7697.txz).

If mentioned methods doesn't work, you could try to use newer GCC version (e.g. current default 4.8 version), by adding USE\_GCC=yes (USE\_GCC=4.8) or changing CC, CXX, etc. values for /etc/make.conf file. You might need to update current ports (e.g. by using portsnap command: portsnap fetch update) to build it (but take a look at /usr/ports/UPDATING file about changes for currently installed software). Remember to comment out USE\_GCC line after building of the devel/upp-nightly port, if you don't intend to use newer GCC for building other ports. (Edit (2016.12.09): The method about USE\_GCC=yes maybe outdated for latest version of port(s), because of USES+=compiler:c++11-lib usage.)

The other method is updating to FreeBSD 10.0-RELEASE version, where LLVM/Clang 3.3 is default compiler (e.g. by using freebsd-update command), but this may require to rebuild/reinstall used software.

(Edit: Previous information may be outdated for newer FreeBSD versions.)

References:

- upp-x11-src-11783.tar.gz source archive from Nightly builds page.
- upp-nightly-11783.tar.bz2 archive from attachments with upp-nightly port for 11783 revision, which contents you may extract to /usr/ports/devel directory.
- upp-nightly-7697.txz package for FreeBSD 9.3-RELEASE-p2 amd64 (for about 30 days after publication date).
- upp-nightly-7697.log with poudriere build log (for about 30 days after publication date).
- GCC48.bm file for GCC 4.8 build method.

Toggle information about previous edits

Edit: Updated to 7703 revision with some fixes to port's Makefile.

The method about newer GCC 4.8 version doesn't work on FreeBSD 10 for some reason. TheIDE compiles, but runs with "segmentation fault (core dumped)" console message. While LLVM/Clang version compiles and runs without errors for single-threaded TheIDE.

Edit (2014.10.15): Updated to 7782 revision.

As it turned out, the FreeBSD 9.3 has LLVM/Clang 3.4.1 compiler by default. The next FreeBSD 10 version, which has the same compiler is 10.1. So, it also possible update to FreeBSD 9.3 from 9, in your case.

Edit (2014.12.10): Updated to 7957 revision. To note: consider to add /usr/local/lib/glib-2.0/include to builder INCLUDE directories, if not used generated GCC.bm file.

Edit (2014.12.26): Updated to 8007 revision.

Edit (2015.02.16): Updated to 8182 revision. Fixed issue with empty directories for dynamic package list.

Edit (2015.03.15): Updated to 8263 revision. Added creation of CLANG build method (CLANG.bm file).

Edit (2015.04.06): Updated to 8323 revision.

Edit (2016.12.09): Updated to 10528 revision. The generated GCC.bm and CLANG.bm (build methods) were changed. You may need to update build methods (\*.bm files) in ~/.upp/theide directory (if exists).

Edit (2017.01.15): Updated to 10703 revision.

Edit (2017.02.11): Updated to 10842 revision. Added SCD port's option for installation of spelling dictionaries (\*.scd files). Added IDE and UMK port's options for building/installation of theide and/or umk.

Edit (2017.02.16): Updated to 10854 revision.

Edit (2017.09.23): Updated to 11340 revision.

Edit (2017.12.15): Updated to 11551 revision.

Edit (2018.02.15): Updated to 11783 revision.

## File Attachments

1) [upp-nightly-11783.tar.bz2](#), downloaded 280 times

---

---

Subject: Re: Latest TheIDE builds fail to execute under FreeBSD

Posted by [Sender Ghost](#) on Tue, 17 Feb 2015 08:55:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello, Pavel.

I have updated the upp-nightly port's archive after Mirek's topic about "Release candidate 2015.1".

In general, the update to newer version looks like follows (with examples for make command):

1. Change PORTVERSION to available U++ revision number for port's Makefile.

2. Switch to root credentials (e.g. with su command), if needed. Run following command to fetch distfile to DISTDIR:

```
# make NO_CHECKSUM=1 fetch
```

3. Return to regular user (e.g. with exit command), if needed. Generate new distinfo file for distfile in step 2:

% make makesum

Also, there is a possibility to check the port installation before install with following command:

% make check-plist

If there are no errors, then the port is ready to install with "make install" command.

Also possible to create package (in work/pkg directory) for installation with using "make package" command. The "pkg add package.txz" may be used for package installation, where "package.txz" is a name of (or path to) created package.

The "make clean" command is used to remove port's intermediate files and directories.

The "make deinstall" command is used to remove installation, for example, before running "make install" command, in case of already installed port.

There are ports, which simplifies installation, e.g. portmaster:

```
# portmaster -Bd devel/upp-nightly
```

---

---

Subject: Re: Latest TheIDE builds fail to execute under FreeBSD

Posted by [Sender Ghost](#) on Fri, 09 Dec 2016 06:25:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Updated devel/upp-nightly port's archive.

Edit: Attached archive was removed. Building of umk integrated into devel/upp-nightly port.

---