
Subject: [solved] Can we get the private members of TreeCtrl made protected?

Posted by [cbpporter](#) on Tue, 16 Jun 2015 13:59:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

I created a custom TreeCtrl than only overrides Paint for prettier display of a list of trees and some members used by Paint are private.

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [koldo](#) on Wed, 17 Jun 2015 07:04:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

Could you show some pictures of it?

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [cbpporter](#) on Wed, 17 Jun 2015 09:10:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

Sure!

I created a custom TreeCtrl. Normally, the tree control is designed for a single root kind of structure. Even when not displaying the root node, there is still a line pointing upwards and it looks like a tree.

My change is about making it behave like a list of trees. Each entry in that list is a root of a tree, but they do not have a parent. I also changed the way lines are displayed for children nodes, enhanced IMHO for minor aesthetics.

In my particular case, I use this tree control to display folders from a classpath. That's why some folders are amrked with an "x", to show that they are invalid.

I implemented this only changing a few lines in the TreeCtrl::Paint override.

If you wish, I can give you the exact members than need to be made protected.

File Attachments

1) [tree.png](#), downloaded 739 times

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [cbpporter](#) on Thu, 02 Jul 2015 12:01:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

Here is the list of things I need protected for my Paint:

protected:

```
struct Item : Node {  
    union {  
        int      parent;  
        int      freelink;  
    };  
};
```

```
bool      free;  
bool      isopen;  
bool      sel;  
Vector<int> child;  
int       linei;
```

```
Size GetValueSize(const Display *treedisplay) const;  
Size GetCtrlSize() const;  
Size GetSize(const Display *treedisplay) const;
```

```
Item() { isopen = false; linei = -1; parent = -1; canselect = true; sel = false; free = false; }  
};
```

```
struct Line : Moveable<Line> {  
    int level;  
    int itemi;  
    int ll;  
    int y;  
};
```

```
ScrollBars sb;  
Scroller  scroller;  
bool      nobg;  
int       levelcx;  
bool      noroot;  
Vector<Line> line;  
Array<Item> item;  
int       dropitem, dropinsert;  
bool      highlight_ctrl;  
int       cursor;  
bool      nocursor;  
bool      multiselect;
```

```
const Display *display;
```

```
int FindLine(int y) const;  
const Display *GetStyle(int i, Color& fg, Color& bg, dword& st);
```

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [mirek](#) on Sun, 12 Jul 2015 07:51:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

I do not know. Generally, things are private to maintain narrow interface. If they become protected, they become part of interface.

OTOH, I like the functionality you propose. I suggest adding this to regular TreeCtrl as option... (files please?)

Mirek

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [cbpporter](#) on Thu, 16 Jul 2015 08:37:04 GMT

[View Forum Message](#) <> [Reply to Message](#)

How about this?

File Attachments

1) [TreeCtrl.cpp](#), downloaded 316 times

2) [TreeCtrl.h](#), downloaded 594 times

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [mirek](#) on Fri, 28 Aug 2015 06:33:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

Sorry for the delay... applied.

However:

```
op -= Ctrllmg::cross().GetSize() / 2;  
w.DrawImage(op.x, op.y, imgEmpty);
```

Should not that be rather

```
op -= imgEmpty.GetSize() / 2;  
w.DrawImage(op.x, op.y, imgEmpty);
```

?

Also, perhaps RenderMultiRoot should call NoRoot?

I have added docs, please check them too...

Mirek

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [cbpporter](#) on Fri, 28 Aug 2015 10:51:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thanks!

Use any name that you think is best. I can adapt. Now if we resolve the TimeStopHR, I can use stock U++ again :).

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [mirek](#) on Sat, 29 Aug 2015 05:15:04 GMT

[View Forum Message](#) <> [Reply to Message](#)

cbpporter wrote on Fri, 28 August 2015 12:51Thanks!

Use any name that you think is best. I can adapt. Now if we resolve the TimeStopHR, I can use stock U++ again :).

Ops, looks like I have not explained myself well... (english not being my native language).

Please, what I ask about is not about names, but semantics:

- using imgEmpty dimension for calculation in TreeCtrl::Paint instead of surrogate 'cross'
- calling ('executing') NoRoot in RenderMultiRoot (becuse I believe that you need to call NoRoot anyway to make it active).

Mirek

Subject: Re: Can we get the private members of TreeCtrl made protected?

Posted by [cbpporter](#) on Mon, 31 Aug 2015 10:35:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

Oh, I see now.

Using "imgEmpty" for size calculations is indeed better.

As for calling NoRoot, this will have the side effect of forcing the display of the empty node icon for all users who call NoRoot right? That's partially why I added a new flag.
