
Subject: Cannot use Format for unsigned int
Posted by [deep](#) on Wed, 26 Apr 2017 05:18:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi

Using Win10, MSC15
UPP10943

```
#include <Core/Core.h>
```

```
using namespace Upp;
```

```
CONSOLE_APP_MAIN
{
    int n;
    unsigned int un;
    String s;
```

```
n = 1212;
un = 0x05060708 ;
```

```
DUMP(n);
DUMP(un);
```

```
s << Format("%08X" , n) << "\n";
s << Format("%08X" , un) ;
```

```
DUMP(s);
```

```
}
```

I get compile time error

'Upp::Format': none of the 45 overloads could convert all the argument types
for unsigned int variable un

TestFormat.cpp(18): error C2665: 'Upp::Format': none of the 45 overloads could convert all the
argument types
\upp\uppsrc\core\Format.h(111): note: could be 'Upp::String Upp::Format(const char *,const
Upp::Vector<Upp::Value> &)'
\upp\uppsrc\core\Format.h(106): note: or 'Upp::String Upp::Format(const char *,const
Upp::Value &)'
\upp\uppsrc\core\TimeDate.h(154): note: or 'Upp::String Upp::Format(Upp::Time,bool)'
\upp\MyApps\TestFormat\TestFormat.cpp(18): note: while trying to match the argument list '(const
char [5], unsigned int)'
TestFormat: 1 file(s) built in (0:04.82), 4828 msec / file, duration = 4844 msec, parallelization

0%

MinGW error

error: conversion from 'unsigned int' to 'const Upp::Value' is ambiguous
s << Format("%08X", un) ;

Subject: Re: Cannot use Format for unsigned int
Posted by [deep](#) on Wed, 26 Apr 2017 05:27:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi

Looking at Value.cpp code I see there is no unsigned types.
This may be the cause.

How to add "unsigned int" -- uint32 and uint64

```
void Value::RegisterStd()
{
ONCELOCK {
    Value::Register<WString>("WString");
    Value::Register<Complex>("Complex");
    Value::Register(VALUEARRAY_V, ValueArrayDataCreate, "ValueArray");
    Value::Register(VALUEMAP_V, ValueMapDataCreate, "ValueMap");
    Value::AddName(STRING_V, "String");
    Value::AddName(INT_V, "int");
    Value::AddName(DOUBLE_V, "double");
    Value::AddName(VOID_V, "void");
    Value::AddName(DATE_V, "Date");
    Value::AddName(TIME_V, "Time");
    Value::AddName(INT64_V, "int64");
    Value::AddName(BOOL_V, "bool");
    Value::AddName(ERROR_V, "error");
}
}
```

Subject: Re: Cannot use Format for unsigned int
Posted by [mirek](#) on Wed, 26 Apr 2017 06:34:22 GMT
[View Forum Message](#) <> [Reply to Message](#)

Format("%08X", (int)((dword)INT_MAX + 20))

